RECENT TIMING ACTIVITIES AT THE U.S. NAVAL RESEARCH LABORATORY

Ronald Beard, O. Jay Oaks, Kenneth Senior, and Joseph White U.S. Naval Research Laboratory E-mail: Joe.white@nrl.navy.mil

Abstract

The U.S. Naval Research Laboratory has a number of ongoing time and frequency programs. This paper provides an overview of work currently being done. The programs include GPS clock life testing and on-orbit analysis, Distributed Time and Frequency Sustems, and iGPS. An update on UTC (NRL) is also presented.



Timing Related Projects

IGS Related Activities
GPS On-Orbit Analysis
Next Generation GPS Timescale Support (OCX)
Distributed Time & Frequency Simulation Environment
GPS Timing Receiver Calibration
Precise Clock Evaluation Facility (PCEF)
GPS Space Clock Life Testing
High Integrity GPS

Space Applications Branch U.S. Naval Research Laboratory

maintaining the data needed, and c including suggestions for reducing	lection of information is estimated to completing and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding ar DMB control number.	ion of information. Send comments arters Services, Directorate for Information	regarding this burden estimate mation Operations and Reports	or any other aspect of the 1215 Jefferson Davis	nis collection of information, Highway, Suite 1204, Arlington
1. REPORT DATE NOV 2009		2. REPORT TYPE		3. DATES COVE 00-00-2009	red to 00-00-2009
4. TITLE AND SUBTITLE			5a. CONTRACT NUMBER		
Recent Timing Act	ivities at the U.S. Na	ratory	5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)			5d. PROJECT NUMBER		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
	ZATION NAME(S) AND AD th Laboratory,4555 0375	` '		8. PERFORMING REPORT NUMB	G ORGANIZATION ER
9. SPONSORING/MONITO	RING AGENCY NAME(S) A		10. SPONSOR/MONITOR'S ACRONYM(S)		
			11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAIL Approved for publ	LABILITY STATEMENT ic release; distributi	on unlimited			
13. SUPPLEMENTARY NO 41st Annual Precis Santa Ana Pueblo,	e Time and Time In	terval (PTTI) Syste	ms and Applicati	ons Meeting,	16-19 Nov 2009,
14. ABSTRACT see report					
15. SUBJECT TERMS					
16. SECURITY CLASSIFIC	17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF		
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	Same as Report (SAR)	10	RESPONSIBLE PERSON

Report Documentation Page

Form Approved OMB No. 0704-0188



NRL IGS Activities




The International GNSS Service (IGS) is a federation of over 200 agencies


Produces standards and products for application in the geosciences.

NRL chairs the IGS Clock Products Working Group (CPWG)

Primary responsibility of the CPWG is the production of the IGS timescales

Rapid IGS clock products are aligned to IGRT daily Final IGS clock products are aligned to IGST weekly Allows dissemination of IGS time (1 x 10⁻¹⁵ @ 1 d) Dissemination of UTC < 50 ns





IGS timescales are generated from a distributed network of clocks

- Kalman filter implementation
- dynamically weighted clocks
- driven mostly by H-Masers
- IIR Rb clocks ~ 1% each

Tracking Station Clocks:

H-masers (57)

cesiums (32)

rubidiums (30)

Satellite Clocks:

cesiums (7) rubidiums (24)



UT1/LOD Analysis

New Kalman filter for optimally combining VLBI UT1 & GPS LOD

- New filter produces best UT1/LOD as compared to all other similar products by multiple measures including comparison with independent Atmospheric and Oceanic Angular Momentum Data
- Used to support recent U.S. NRC Study
- Code made available

IERS combinations do not use VLBI UT1 & GPS LOD inputs optimally!

fidelity of high-frequency geodetic measurements is degraded

Main Issues: VLBI UT1 & GPS LOD combinations must recognize & mitigate systematic errors


- UT1 from VLBI Intensives has serious baseline- & time-dependent errors
- UT1 from weak VLBI sessions should be rejected
- GPS LODs have bias & harmonic errors that should be modeled

Motivation: IGS real-time orbit predictions require better EOP predictions

- UT1 prediction errors (= RZ rotation errors) dominate real-time performance
- polar motion prediction errors are also significant



New Time Scale - Tie to UTC



Current Version relies on GPS Time for Reference to UTC

Multiple Stations collocated at Timing Centers will provide a better quality and robust link to UTC, relatively calibrated to UTC through Circular T


Stability of the average of these clocks suggest a steering time constant of about 70 days




GPS On-Orbit Analysis

- On Line Databases of all SV and MS tracking data
- Precise measurement data in system and external
- Characterization of SV and MS clocks
- Anomaly investigation Tuning of Filter Q's


Data Source	Data Type	Description		
NGA 15-minute phase		SV clock offsets relative to DOD Master Clock		
NGA	15-minute phase	GPS MS clock offsets relative to DOD Master Clock		
IGS	5-minute phase	SV clock offsets relative to IGS time scale		
IGS	5-minute phase	IGS GPS ground clock offsets relative to IGS time scale		
IGS	5-minute phase	IGS timescale reference data		
NRL analytical results	SV clock discontinuity	SV clock phase, frequency, and drift discontinuities magnitude and epoch		
NRL analytical results	MS clock discontinuity	MS clock phase, and frequency discontinuities magnitude and epoch		
GPS MCS	Time period	SV clock operating periods		
GPS MCS	Time period	SV operating periods		
GPS MCS	Time period	SV position in the GPS constellation		
NRL computed SV eclipse periods		SV periods of time when the earth shadows a portion of the orbit from the sun		
NGA	SV x,y,z trajectory	Precise post-fit SV ephemerides		
IGS	SV x,y,z trajectory	Precise post-fit SV ephemerides		
GS GPS broadcast data		Predicted orbit and clock transmitted in the GPS signal		







On-Orbit Performance



IIA cesiums

- poorest overall stability
- behave mostly as random walk phase noise
- MDEV power-law slope -1/2
- excess deviations near 13,600 s

IIA rubidiums

- similar to Cs clocks but much more stable
- flicker phase component for intervals < 100 s
- also with excess near 13,600 s

IIR & IIR-M rubidiums

- newer generation clocks less stable than IIA Rb up to 1000 s
- complex high-frequency behavior due to onboard Time Keeping System (TKS)
- some excess near 13,600 s

Space Applications Branch U.S. Naval Research Laboratory



Next Generation GPS Timescale

CONTEXT/PROBLEM:

- GPS system functionality relies on stable satellite clocks & the ability to predict them well; individual clock prediction in turn requires a stable reference timescale
- Next Generation GPS operational ground control segment (OCX) now being designed
 - NRL support requested by JPL

Goal / NRL Approach:

- Develop a more stable ensemble timescale
- Leverage existing Kalman filter approaches but with improved clock modeling
- Algorithm developed under ONR funded project
- NRL providing algorithm/code development/testing/consultation

Challenges:

- Intended for operational use
- Must be highly robust against individual clock failures
- Must be adaptive in its determination of model parameters




Distributed Timekeeping

- Current proliferation of single-source (GPS-centric) timekeeping
- A new approach that inter-compares & combines existing embedded timing signals:
 - would enable in-situ determination of performance,
 - improve & make more robust the timekeeping (holdover) capability,
 - provide synchronization,
 - provide integrity feedback to individual systems/sensors,
 - limit single-source failures & vulnerabilities

Requires new theory & algorithms for combining timing signals of very different type & quality through widely varying links

- Clocks perform very differently:
 - in same & different environments
 - over different periods of time (scales)






DTFS Simulation Environment

Distributed Time and Frequency Simulink simulation environment

Used to model distributed common time/frequency architectures


Includes ensemble clock models, timescale algorithms, control loops, and multiple external links






GPS Timing Receiver Calibration








Simulator Calibration

Date/time	Simulator L1 Bias	Simulator L2 Bias	Corrected L1 Receiver Offset	Comments
54222.5	0	4	20.2 nsec	
54236	1	4	22.5 nsec	
54237	0	3	21.1 nsec	

Space Applications Branch U.S. Naval Research Laboratory



GPS Timing Receiver Calibration





Precise Clock Evaluation Facility (PCEF)






Measurement Systems

Dissemination

- **Precise and Accurate Time and Frequency** References
- Maintain realization of Universal Coordinated Time, UTC(NRL)
- · Multiple precise dual mixer phase comparison systems
- Automated data collection and archival systems
- · Precise time/frequency transfer and dissemination systems

 • Multichannel 1PPS evaluation system









UTC (NRL)

Purpose is to support Navy/NRL time & frequency research activities

Unique tool for investigation of time scale algorithms and techniques





Began submitting clock data to BIPM in September '07 under test/evaluation

Official submissions began in January 2008



Space Clock Extended Life Tests

BLOCK IIR RAFS LIFE TEST



1997 - 2005

- · Space-Like Environment (vacuum & temperature)
- Installation in test chambers duplicates mounting in SV Continuous Operation for a minimum of three years
- · Validates SV Telemetry and Control Interface
- Validates operation prior to actual flight in operational SV
- · High precision performance evaluation

BLOCK IIF CESIUM EXTENDED TEST



2004 - Interrupted in 2006



2008 - In process




GPS Block IIF DCBFS Life Test

Began in August 2004

Interrupted in 2006










GPS Block IIF RFS Life Test


Two GPS IIF production clocks, No 5 and 25 are under test

Test configuration improved over that used in prior tests.





Space Applications Branch U.S. Naval Research Laboratory



41st Annual Precise Time and Time Interval (PTTI) Meeting